



Canon

A3 PIXMA HOME TS9565

YOUR A3 CRAFT PRINTER



Wireless

Print with ease with PIXMA Cloud Print and other applications such as Apple AirPrint, Google Cloud Print that simply connect to mobile devices.



Print With New Media

Get creative and use your printer to print on a variety of new mediums such as nail stickers, 12" x 12" card stock (for scrapbooking and card making), 5" x 15" and 3.5" x 3.5" square sizes, restickable and magnetic paper.



A3

Perfect for the home or office, this compact multi function printer with automatic document feeder (ADF) can print up to A3 size without being bulky or appearing oversized.



Redefined inks

Produce crisp text with pigment black, beautiful photos with 5-color independent inks.



Borderless Prints

Print your documents and photos on a range of different paper sizes, from business card to Instagram-style images, on square sizes! You can even print borderless 4"x6" photos in approx. 17 seconds.



Dual Paper Feeder & auto two-sided printing

Get flexible with the way your printer receives paper – either through rear paper feeding or via front paper cassette. The paper output tray is automatically expandable, as well as two sided printing.



Booklet layout printing

Print booklets with ease using A3 and A4 paper. Perfect for holiday itineraries, recipe books, colouring books and your business needs.



Printable Nail Stickers

Change up your look daily and print any picture or pattern on to stick on nail stickers.



SD Card Reader

Print photos off your laptop or camera, with the printer's direct SD card slot - making it easier than ever before to showcase your prints.



Built-In Pattern Paper

45 built-in patterned papers makes creative printing and scrapbooking easy. Print directly from your printer in minutes without the use of your PC.

What inks can I use with my printer?

































Technical Specifications

PIXMA HOME TS9565

i CCIIIIIC	ıı əpcci	incations	I IMMA HOME 133303		
	Туре		Permanent		
Print Head / Ink	Number of Nozzles Ink Tank		Total 4,096 nozzles (PGBK 1,024 nozzles, BK/Y each 512 nozzles, C/M each 1,024 nozzles)		
Maximum Printing	IIIK TUIIK		5-color(C/M/Y/BK/PGBK) 4800 (horizontal)*2 x 1200 (vertical) dpi		
Print Speed	Document : Col*3	ESAT/Simplex	approx. 10.0 ipm		
	Document : B/W ^{*3}	ESAT/Simplex	approx. 15.0 ipm		
	Document : Col ^{*3}	FPOT Ready/Simplex	approx. 10.0 sec.		
	Document : B/W ^{*3}	FPOT Ready/Simplex	x approx. 8.0 sec.		
	Photo (4"x6")*3	PP-201/Borderless	approx. 21 sec		
Printable Width			Up to 298.0mm, Borderless: Up to 304.8mm		
Printable Area	Borderless Printing*4		Top/Bottom/Right/Left margin: each 0 mm		
	Bordered Printing				
	Bordered Auto 2-sided printing		Top margin: 5 mm, Bottom margin: 5 mm, Left/Right margin: 3.4 mm (LTR: Left: 6.4 mm, Right: 6.3 mm)		
Support Media	Rear Tray		Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), High Resolution Paper (HR-101N), Photo Paper Plus Glossy II (PP-301) Photo Paper Pro Luster (LU-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus Semi-gloss (SG-201), Photo Paper Glossy (GP-701) Matte Photo Paper (MP-101), T-Shirt Transfer, Envelope, Greeting Card (manufactured by Avery and RedRiverPaper), Cardstock, Magnetic Photo Paper (MG-101)Restickable Photo Paper (RP-101)		
	Cassette		Plain Paper		
	Multi-purpose Tray		Printable Nail Stickers (NL-101)		
Paper Size	Rear Tray		A4, A5, B5, LTR, LGL, LDR, B4, A3, Envelopes(DL, COM10), Square (5"x5", 4"x4", 3.5"x3.5"), Card Size(91 x 55mm), 4"x6", 5"x7",7"x10", 8"x10", 10"x12", 12"x12" [Custom size] width 55mm - 304.8 mm, length 89mm - 676mm		
	Cassette		A4, A5, B5, LTR [Custom size] width 148.0 mm - 215.9 mm, length 210mm - 297mm		
Paper Size (Borderless)			A4, A3, LTR, LDR, 4"x6",5"x7",7"x10", 8"x10",10"x12", 12"x12"Card Size(91x55mm), Square (5"x5", 4"x4", 3.5"x3.5")		
Paper Handling (Maximum Number)	Rear Tray	Plain Paper (LTR size)	Plain Paper= 100		
		Plain Paper (A4 size)	Plain Paper, Canon Red Label Superior(WOP111) = 100 Canon Oce Office Colour Paper(SAT213) = 80 * A3 size : Plain Paper = 50		
	Cassette	Plain Paper (LTR size)	Plain Paper=100		
		Plain Paper (A4 size)	Plain Paper, Canon Oce Red Label Paper(WOP111)= 100 Canon Oce Office Colour Paper(SAT213) = 80		
	Multi-purpose Tray		1sheet (manual bypass)		
Support Media for Auto 2-sided printing	Туре		Plain Paper		
	Size		A4, A5, B5, LTR		
Paper Weight	Rear Tray		Plain Paper: 64-105 g/m2 , Canon specialty paper: max paper weight : approx. 300 g/m2 (Photo Paper Pro Platinum PT-101)		
Ink End Sensor	Cassette		Plain Paper: 64-105 g/m2 Dot count		
Print Head Alignment			Auto/Manual		



Technical Specifications

PIXMA HOME TS9565

	Scanner Type			Flatbed
	Scanning Method			CIS
ž Ž	Optical Resolution*6	*Optical resolution scan is available, only when you use TWAIN Driver.		1200 x 2400 dpi
COPY	Scanning Bit Depth	Grayscale		16bit/8bit
	(Input/Output)	Color		RGB each 16bit/8bit
	Maximum Document Size	Flatbed		A4/LTR(216 x 297mm)
		ADF		A4/LTR/LGL
	Maximum Document Size	Size		A4/LTR A4/A5/B5/LTR/LGL/B4/A3/11"x17"/LDR/4"x6"/5"x7"/Square (5" x 5")/Card Size(91 x 55mm)/Disc Label
	Compatible Media	Туре		Plain Paper, Photo Paper Pro Platinum (PT-101), Photo Paper Pro Luster (LU-101), Photo Paper Plus semi-gloss (SG-201), Photo Paper Glossy (GP-701), Matte Photo Paper(MP-101), Photo Paper Plus Glossy II (PP-301), Printable Disc
	Image Quality			3 positions (Draft, Standard, High)
	Density Adjustment			9 positions, Auto intensity(AE copy)
		Document : Color	sFCOT/Simplex	approx. 19 sec.
	Copy Speed*10		sESAT/Simplex	
	copy speed	Document (ADF) : Color	ESAT/Simplex	approx. 8.0 ipm
		Document (ADF) : Black	ESAT/Simplex	approx. 14.0 ipm
	Multiple Copy	Black/Color		max. 99 pages TCP/IP
	Protocol	Naturals Tuna		IEEE802.3u(100BASE-TX)/IEEE802.3(10BASE-T)
	Wired LAN	Network Type Data Rate		10M/100Mbps (auto switchable)
		Network Type		IEEE802.11n/IEEE802.11g/IEEE802.11b
		Frequency Band		2.4GHz
>		Channel 29		1-13
Ž	Wireless LAN	Range		indoor 50m (depends on the transmission speed and conditions)
		9-		WEP64/128bit
		Security		WPA-PSK(TKIP/AES)
				WPA2-PSK(TKIP/AES)
	Direct connection(Wireless LAN)			Available
	Bluetooth			Available
	AirPrint			Available
		Layout	bordered/borderl es*15)	LTR,A4,4"x6",5"x7",8"x10",Square (5"x5", 4"x4", 3.5"x3.5"), Card Size(91 x 55mm) , 7"x10, A3, LDR,10"x12", 12"x12"
		D 1 1 0 1 1 1 1 1 2	(bordered only)	A5, B5, LGL, #10 Envelope, DL Envelope, Disc Label, B4, Custum size
	Windows 10 Mobile, Mopria, Google Cloud Print, Canon Print	Print Quality 12		Standard/High Available
	Service, PIXMA Cloud Link			
Ë	Canon PRINT Inkjet/SELPHY	I more de	1	Available
Printing Solutions	(for iOS/for Android)	Layout	1-up (bordered/borderl es ^{*15})	LTR, A4, 4"x6", 5"x7", 8"x10",Square (5"x5", 4"x4", 3.5"x3.5"),Card Size(91 x 55mm) ,A3, 10"x12",12"x12"
intin			1-up(bordered only)	A5, B5, LGL,B4
Ē	Camera Direct Spec.	Compatible Digital Camera Connecting type		"PictBridge" compliant digital cameras, camcorders and camera phones LAN/ WLAN
		File Format		JPEG (Exif ver2.2/2.21/2.3 compliant)*18, PNG
	Card Direct Spec.	Compatible Storages		SD Card, SDHC Card, SDXC Card, miniSD Card*11, micro SD Card*11 mini SDHC Card*11, micro SDHC Card*11, microSDXC Card*11
		File Format		JPEG and TIFF (Exif-compliant) taken by DCF(Ver.1.0/2.0) compliant digital cameras. (Exif ver2.2/2.21/2.3 compliant)
		Storage function*14	READ Function	Available
		•	WRITE Function	Available
	Operation Panel	Display		LCD (4.3 inch/10.8 cm TFT color)
tions	ADF	Paper Handling (Plain Paper)		A4/LTR=20 sheet LGL=5 sheet
	Interface	Auto Duplex		N/A Hi-Speed USB
	Interface	USB B Port Card Slots		Available
		Wireless LAN		Available
	PictBridge	LAN		Available
		USB		N/A
	Self-opening Paper Output Tray			N/A
ij	Quiet Mode			Available
pe	Acoustic Noise (PC Print)	Plain Paper(A4, B/W)* ²⁷		Approx. 49.5 dB(A)
ls 1	Power			AC 100-240V 50/60Hz
ero		OFF		Approx. 0.3 W
en	Power Consumption	Standby		Approx. 2.0 W
0		Copying*28		Approx. 14W
	Dutu Cuala	USB connection to PC		
	Duty Cycle	Eactory configuration		25,000 Sheet
		Factory configuration	mm	Approx. 468 x 366 x 193 mm
	Dimension(WyDyH)	Paner installed (cassotta)	mm	As of factory configuration
	Dimension(WxDxH)	Paper installed (cassette) Output/ADE traus extended	mm mm	As of factory configuration Approx 468 x 820 x 373 mm
	Dimension(WxDxH) Weight	Paper installed (cassette) Output/ADF trays extended kg	mm mm	As of factory configuration Approx. 468 x 820 x 373 mm Approx. 9.7 kg



- *2: Ink droplets can be placed with a pitch of 1/4800 inch at minimum
- 2. This indigites during placet of interpolation and place of paper used etc.
- "5: TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

 "6: Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

 "8: The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.

- *10: Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.
- *11: Can be used by attaching the adapter that is separately sold in the market.
- *12: Resolution may be changed between Direct print and printing from PC. *14: It is NOT supported via Network.
- 15: The amount of image extension beyond the paper cannot be adjusted.
- *16: Plain paper is printed bordered automatically, regardless of the camera settings.
- 17: Not supported for disk label print.

 18: Image data taken by DCF (Ver.1.0/2.0) -compliant digital cameras, camcorders or camera phones and recorded in JPEG (Exif-compliant) format.
- *19: Function depends on the connected digital cameras, camcorders or camera phones. *20: Only 'high' mode available as for the printer without LCD.
 *23: "Non-support for 2/4/9/16-up in sticker printing as well as date/file number printing in disc label printing. As for '4-up' print layout, either file number or date can be printed at one time."
- *24: The performance of the printer may be reduced under certain temperature and humidity conditions
- *25: For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions. *26: When printing ISO/JIS-SCID N2 on 4"x6" Photo Paper Plus Glossy II using default settings.
- *27: Acoustic Noise is measured based on ISO7779 standard with default setting.
- *28: Copy:When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. Specifications are subject to change without notice. *29: 1-11 in US, CND, LTN, BRA, TW and HK.
- 31: Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Color document fax transmission speed is based on default setting using Canon Color Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.

 *32: Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.

 *33: Not supported for AirPrint.

- *34: Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program '35: Not supported for 'Printable Nail Stickers'.

Standard disclaimers

- If your inkjet printer is found defective within the applicable manufacturer warranty period (1 Year), we'll replace it with the same, or an equivalent model. Excludes damage caused by external factors, Canon's full replacement promise is in addition to your rights under Australian Consumer Law which, depending on the type of fault, includes repair, replacement or a refund. For full terms see: www.canon.com.au/printassist or the card in the printer box. Only for products purchased at Authorised Canon Australia retailers
- Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- · USB cable not included

Note: A complete set of ink cartridges with ink available in each cartridge is required for all functions including copy, print and scan. Some functions (e.g. PIXMA Cloud Link, scan to cloud or scan to email) may not work unless genuine Canon inks are used and/or an internet connection established.

